
9023 TOP RAIL **DECK MOUNT** 3 3/8" 9023 ALUMINUM TOP RAIL 9017 ALUMINUM SNAP POCKET (4) $\#12 \times 1"$ PAN HEAD SMS 410SS STND. COMM. **(** (+/- TOP RAIL PROFILE VARIANCE) (**o**) / 42" 9005 ALUMINUM POST $1\frac{3}{4}$ " **(** STND. RES. 1x19 316 SS CABLE 0 **GROMMET** 36" **©** FIELD FASTENERS MEETING LOAD REQUIREMENT-BY OTHER 9026R/05 ALUMINUM BASE PLATE BLOCKING REQUIRED TO MEET LOAD

REQUIREMENTS BY

OTHER



GENERIC DETAILS. ACTUAL DESIGN AND MAKE—UP VARY AS REQUIRED. BASE PLATE PARALLEL STND. PERPENDICULAR MAY BE REQUIRED



9026R BASE PLATE



9023 TOP RAIL & 9005 POST

CrystaLite railings are structurally designed and stamped by an independent structural engineer. CrystaLite railing systems have been rated to accommodate high wind loads and exposure ratings set forth by local building codes. CrystaLite will select the appropriate post size and spacing to meet code requirements, exposure criteria, with wind speeds up to 120 mph.