Dealer:	Da	Date: Quote Only Dealer PO		
Attn:	Phone:	Fax:		
SERIES 1100 SMOKE VENTS ORDER FORM				

UL 793 CERTIFIED DOUBLE LID SINGLE LID SINGLE LID **DOUBLE LID CURB MOUNT** SELF FLASHING CURB **CURB MOUNT** SELF FLASHING CURB QTY □9" tall □ 9" tall □ 12" tall □ 12" tall HEIGHT NA NA □ 48" x 48" □ 48" x 48" □ 48" x 96" □ 48" x 96" □ 48" x 96" STANDARD SIZE □ 48" x 96" □ 37" x 75" □ 37" x 75" **ROUGH OPENING** OUTSIDE CURB DIM □ 46.25" x 69.5" □ 46.25" x 69.5" 51.5" x 99.5" □ 46.25" x 89.5" □ 46.25" x 89.5" NOMINAL 4' x 8' SIZE ONLY OUTSIDE CURB DIM **ROUGH OPENING** OUTSIDE CURB DIM **ROUGH OPENING CUSTOM SIZE** □ 51.5" x **□** 48" x Non-Insulated Non-Insulated Acrylic Acrylic □ clear □ clear Insulated Insulated ■ white □ white Co-Polyester / Acrylic Co-Polyester / Acrylic **GLAZING** □ clear / clear □ clear / clear Insulated Insulated Co-Polyester / Acrylic Co-Polyester / Acrylic ■ white / clear ■ white / clear □ clear / clear □ clear / clear □ white / clear ■ white / clear ☐ 165° UL Listed Link □ 212° UL Listed Link **FUSIBLE LINK** □ 286° UL Listed Link □ 350° UL Listed Link exterior included exterior included exterior included exterior included MANUAL RELEASE ■ add interior □ add interior □ add interior □ add interior OPTIONAL ACCESSORIES ☐ ELITE (cable) ☐ ELITE (cable) **FALL PROTECTION** □ ELITE (cable) ☐ ELITE (cable) SAFETY GRID ☐ SENTRY (bar) ☐ SENTRY (bar) ☐ SENTRY (bar) ☐ SENTRY (bar)



EVERETT SPC

phone: 1-800-666-6065 fax: 425-258-6734

SPOKANE

phone: 1-800-382-5403 fax: 509-921-2137 SALEM

phone: 1-800-664-1257 fax: 503-391-0974



Series 1100 Smoke and Heat Vent

CrystaLite's Smoke Vents are made with aircraft grade 6063-T5 aluminum, with welded corners on internal and external framing members, which provides maximum durability and a weather tight enclosure.

Mounting

Smoke Vents are a curb mounted product, with the option of being provided with self-flashing insulated curbs. CrystaLite's Smoke and Heat Vents, and self-flashing insulated curbs, are available in both standard and custom sizes.

Glazing

Domes are made with high impact resistant co-polyester sheeting and impact modified acrylic. Domes are available in two color options, clear for maximum light and translucent white for optimal light diffusion.

Releases

UL Listed fusible links release the smoke vent lid automatically when the internal heat of the building reaches that of the fusible link's specified temperature. External manual releases are included, internal manual release is optional.

Estimated Dealer Cost	
quote good for 30 days	