
# SIDE MOUNT (FASCIA) WORKSHEET

# This Side Mount Worksheet is REQUIRED for ALL ORDERS when Side Mount is requested Please fill out seperate sheets if different post dimensions are required for same job. # of Posts Recommended 1" From Edge of Rim Joist **BASIS OF** TOP HOLE **ENGINEERING** FROM TOP OF DECK **BOTTOM HOLE BASIS OF ENGINEERING** FROM TOP OF DECK 8" **POST LENGTH BELOW BASIS OF ENGINEERING** FROM TOP OF DECK 9" Recommend 1/2" min. from bottom of Fascia. ☐ Flush □ Offset ☐ Custom 3/8" Tvp.





# **FASTENERS**

CrystaLite cannot specify field fasteners for your project. Below is a list of available fasteners we can provide and may be used, if the installer verifies that they are sufficient for this specific application.

It is the installer's responsibility to determine mounting fastener sizes and confirm that base plate or side-mount post compression stresses and mounting fastener tension values are acceptable for the materials to which the rail system is attached.

☐ FASTENERS NOT BY CRYSTALITE (DEFAULT)

## **DECK MOUNT FASTENERS**

- ☐ #14 x 3" PHSMS
- ☐ #14 x 4" PHSMS
- ☐ 3/8" x \_\_\_\_\_ (additional machining costs)

### SIDE MOUNT FASTENERS

### LAG INTO BLOCKING

- ☐ 1/4" x 3" SS Lag Screw
- ☐ 1/4" x 4" SS Lag Screw
- □ 1/4" x \_ SS Lag Screw
- □ 3/8" x \_\_\_\_\_

### THROUGH BOLTS W/ NUT & WASHERS

- □ 1/4"-20 x 2-1/2" SS
- □ 1/4"-20 x 3" SS
- □ 1/4"-20 x 3-1/2" SS
- □ 1/4"-20 x 4" SS
- ☐ 1/4"-20 x \_\_\_\_ SS
- □ 3/8"-16 x \_\_\_\_\_

### **CONCRETE APPLICATIONS**

- ☐ 1/4"-20 x 3-1/4" SS Wedge Anchor
- ☐ 3/8"-16 x 3-3/4" SS Wedge Anchor