

Dealer:	Date:	<input type="checkbox"/> Quote Only <input type="checkbox"/> Dealer PO
Attn:	Phone:	Fax:
ROOF ACCESS HATCH ORDER FORM		

ROOF ACCESS HATCH

Remember, safety first! We have taken the traditional design of the Roof Access Hatch and brought today's newest safety innovations to the roof.

The Roof Hatch is coated with an electrostatically applied, thermally-fused powder coat in high gloss Safety Red finish, meeting Federal Spec. #11105 for safety red warning color.

This finish not only allows you to visually locate the hatch from a much greater distance than a normal primer coated hatch, but also alerts anyone on the roof that there is a roof opening nearby. Additionally, with the lid in the open position there is a specially designed visual warning signal alerting you that the hatch is open.

General Specs

Roof access hatch shall be model 3036-RAH-SF, and shall have a safety red electrostatically applied thermally-fused high gloss powder coat finish. A yellow and black striped visual warning signal shall be on top, front of curb and on inside of lid. The roof safety hatch shall measure 30" x 36" x 14" inches.

- High-gloss thermally-fused, powder-coat finish for durability and corrosion protection.
- 30"x 36" standard size, call for quote on custom sizes.
- Visual warning signal when hatch is opened.

Curb Construction

The curb shall be 14 Ga. galvanized steel with 1" fiber board insulation and shall be 12" in height with a 3-1/2" flange and mounting holes for roof attachment; integral cap flashing of the same material and thickness as the curb. Curb and cap flashing shall be fully welded at the corners for a watertight construction. Hinges are two piece formed steel with a non-removable heavy duty pivot pin.

ROOF HATCH SAFETY GUARDS

Aluminum Guard Rails are designed and tested to provide fall protection for workers near an open access roof hatch. The system features removable side Guard Rails and Chain Gates, to allow for maximum egress and passage of large equipment.

Safety Criteria

Guard Rails and Chain Gates system has been tested by an accredited independent test laboratory, as typically installed on a roof hatch, to meet the following standards: OSHA 1910.23, 1910.27, ANSI A1264.1.

Installation

Guard Rails are installed on the roof hatch directly, which eliminates the need for extra holes to be drilled on to the roof surface. The mounting bracket is designed to align with accessory holes on typical roof hatches.



Roof Access Hatch



Roof Hatch Safety Guards

ORDER FORM

QTY	ITEM
	30" x 36" Roof Hatch - Red
	Safety Guards - Mill Finish

Estimated Dealer Cost
quote good for 30 days



EVERETT
 phone: 1-800-666-6065
 fax: 425-258-6734

SPOKANE
 phone: 1-800-382-5403
 fax: 509-921-2137

SALEM
 phone: 1-800-664-1257
 fax: 503-391-0974